

41. An apparatus for testing a sample of biologic fluid, said apparatus comprising:  
a container that includes:

a chamber for quiescently holding the sample during the test;

one or more features operable to enable the testing of the sample, wherein at least one of the one or more features is positioned at a known spatial location within the chamber; and

a label containing information which is used in the performance of the one or more tests on the sample, wherein the information includes the spatial location of the at least one feature located within the chamber; and

a reader module operable to perform the testing of the sample, wherein the reader module includes:

a label reader for reading the label, and thereby accessing the information including the spatial location of the at least one feature located within the chamber;

a field illuminator for selectively illuminating a field of the sample quiescently residing within the chamber, wherein the sample field has a known or ascertainable area;

an image dissector, for converting an image of light passing through or emanating from the sample field into an electronic data format useful for test purposes; and

a positioner operable to selectively change the relative position of any or all of the chamber, the field illuminator, and the image dissector, to enable imaging of a field of the sample in which the at least one feature at a known spatial location within the chamber is positioned.

42. The apparatus of claim 41, further comprising means for determining one of a through-plane thickness or a volume of the sample field.

10023405-1234001

43. <sup>3</sup> An apparatus for testing a sample of biologic fluid, said apparatus comprising:  
a container having a chamber for quiescently holding the sample during the test, and  
one or more features operable to enable the testing of the sample, wherein at least one of the  
one or more features is positioned at a known spatial location within the chamber; and  
5 a reader module operable to perform the testing of the sample, wherein the reader  
module includes a field illuminator for selectively illuminating a field of the sample  
quiescently residing within the chamber during the test, an image dissector for converting an  
image of light passing through or emanating from the sample field into an electronic data  
format useful for test purposes, and a positioner operable to selectively change the relative  
position of any or all of the chamber, the field illuminator, and the image dissector to enable  
imaging of the field of the sample in which the at least one feature at a known spatial location  
within the chamber is positioned.

44. <sup>4</sup> The apparatus of claim 43, further comprising means for determining one of a  
through-plane thickness or a volume of the sample field.

45. <sup>5</sup> An apparatus for testing a sample of biologic fluid quiescently residing within a  
chamber, said apparatus comprising:  
a field illuminator for selectively illuminating a field of the sample, said field having a  
20 known or ascertainable area;  
an image dissector for converting an image of light passing through or emanating from  
the field of the sample into an electronic data format useful for test purposes;  
a positioner operable to selectively change the relative position of any or all of the  
chamber, the field illuminator, or the image dissector, thereby enabling selective illumination  
25 of a plurality of the sample fields within the chamber; and  
means for determining one of a through-plane thickness or a volume of each sample  
field.

10023405-15401  
46. <sup>b</sup> The apparatus of claim 45 further comprising means for spatially locating the relative positions of any or all of the chamber, the field illuminator, or the image dissector, to enable selective imaging of any particular spatial location within the chamber.

5 47. <sup>7</sup> An apparatus for testing a sample of biologic fluid, said apparatus comprising:  
a container that includes a chamber for quiescently holding the sample during the test, and one or more features operable to enable the testing of the sample, wherein at least one of the one or more features is positioned at a known spatial location within the chamber;  
a field illuminator for illuminating a portion or all of the chamber;  
an image dissector for converting an image of light passing through or emanating from the sample into an electronic data format useful for test purposes; and  
means for determining one of a through-plane thickness or a volume of each sample field.

48. <sup>8</sup> A method for testing a sample of biologic fluid, comprising the steps of:  
providing a container for holding the sample, the container having one or more features operable to enable the testing of the biologic fluid sample, at least one of which features is located at a known spatial location within the chamber;  
depositing the sample within the chamber, wherein the sample quiescently resides in the chamber thereafter during the test;  
providing a field illuminator for selectively illuminating a portion, or all, of the sample within chamber;  
selectively imaging a portion or all of the illuminated sample, and thereby creating an image of the illuminated sample;  
25 identifying a portion of the image aligned with the at least one feature located at a known spatial location within the chamber.

49. 9 A method for testing a sample of biologic fluid, comprising the steps of:  
providing a container for holding the sample, said container having a chamber with a  
first wall and a transparent second wall;  
providing one or more features operable to enable the testing of the sample, wherein at  
5 least one of the features is located at a known spatial location within the chamber;  
depositing the sample within the chamber, wherein the sample thereafter quiescently  
resides in the chamber during the test;  
providing a reader module that includes a field illuminator for selectively illuminating  
a portion or all of the sample disposed in the chamber, and an image dissector;  
10 selectively change the relative position of any or all of the chamber, the field  
illuminator, or the image dissector to enable selective imaging of one or more sample fields  
within the chamber aligned with the one or more features at known spatial locations;  
selectively imaging the one or more sample fields that contain the one or more  
features.